



















MayTex-Acryl with Texgard impregnation

- material: 100% polyacrylic, spun-dyed, weight 300g/m²±5%
- water column (fabric water tightness) 370 mm, European standard EN 20 811
- colour fastness: grade 2-7 (against bleaching), tested acc. to standard EN ISO 105-B02 (1+ min., 8+ max.)
- protection against UV rays: UPF 40-80, tested acc. to UV standard 801 (cf. page 135 for individual values)

- weather-proof, high and low temperature resistant
- Texgard impregnation gives effective protection against oil, grease, mildew and algae, industrial pollution, exhaust fumes and other negative environmental factors
- tested acc. to Öko-Tex standard 100
- imprinted ads: on parasol canopy and valance in durable, brilliant screen-printing quality
- cleaning: easy to clean with CleanoMay 13, even when mounted

 SA 314 010 white similar to RAL 9003 bordering 00 white	 SA 314 018 white/grey knopped similar to RAL 9016 bordering 00 white	 SA 314 580 white, yellow/grey knopped similar to RAL 9002 bordering 18 silver
 SA 314 344 multi-colour similar to RAL 7035 bordering 18 silver	 SA 314 471 silver-grey/dark brown knopped similar to RAL 1013/7006 bordering 18 silver	 SA 314 030 light grey ★ NEW! similar to RAL 7047 bordering 18 silver
 SA 314 364 telegrey/white similar to RAL 7046 bordering 147 opal	 SA 314 044 grey/white similar to RAL 7004 bordering 18 silver	 SA 314 325 ecru similar to RAL 1013 bordering 52 nature
 SA 314 033 ivory similar to RAL 1013 bordering 20 ivory	 SA 314 583 yellow, grey/yellow knopped similar to RAL 1023/1013 bordering 18 silver	 SA 314 045 pyrite similar to RAL 1002 bordering 10 pyrite
 DA 7560 light yellow similar to RAL 1023 bordering 10 pyrite	 SA 314 003 yellow similar to RAL 1023 bordering 32 yellow	 SA 314 014 mandarin similar to RAL 1033 bordering 79 mandarin
 SA 314 038 beige similar to RAL 1019 bordering 11 beige	 SA 314 008 ochre similar to RAL 1034 bordering 15 ochre	 SA 314 019 terracotta similar to RAL 2012 bordering 48 terracotta

 SA 314 002 orange similar to RAL 2004 bordering 81 orange	 SA 314 001 cherry similar to RAL 3020 bordering 85 cherry	 SA 314 347 ruby similar to RAL 3003 bordering 85 cherry
 SA 314 022 rust similar to RAL 2001 bordering 83 rust	 SA 314 763 bordeaux similar to RAL 3004 bordering 86 bordeaux	 DA 7244 lime green ★ NEW! similar to RAL 6018 bordering 42 lime green
 SA 314 624 green patina similar to RAL 6000 bordering 162 green patina	 SA 314 362 dark green similar to RAL 6005 bordering 95 dark green	 SA 314 257 green/black similar to RAL 6012, bordering 95 dark green
 SA 314 011 royal blue similar to RAL 5010 bordering 62 royal blue	 SA 314 546 blue patina similar to RAL 5007 bordering 187 blue patina	 SA 314 006 sapphire similar to RAL 5002 bordering 66 sapphire
 SA 314 474 navy blue similar to RAL 5013 bordering 91 navy blue	 SA 314 271 navy blue/black similar to RAL 5011, bordering 91 navy blue	 SA 314 016 dark brown similar to RAL 8017 bordering 27 dark brown
 DA 8779 olive brown similar to RAL 7002 bordering 9533 olive brown	 DA 7559 taupe similar to RAL 7006 bordering 926 taupe	 DA 8203 grey basalt similar to RAL 7010 bordering 97 grey basalt
 SA 314 154 black similar to RAL 9017 bordering 19 black		

The shades shown here are not in accordance with the original ones.
If requested, we will be pleased to send you a collection of original cloth samples.

MayTex-Poly

- material: 81% polyester, 19% polyacrylics, weight 230 g/m² ± 5%
- water column (fabric water tightness) 1000 mm, European standard EN 20811
- colour fastness: grade ≥ 7 (against bleaching), tested acc. to standard EN ISO 105-B02 (1= min., 8= max.)
- protection against UV rays: UPF80, tested acc. to UV standard 801 (cf. page 135 for individual values)
- Texgard impregnation gives effective protection against oil, grease, mildew and algae, industrial pollution, exhaust fumes and other negative environmental factors
- tested acc. to Öko-Tex standard 100
- imprinted ads. on parasol canopy and valance in durable, brilliant screen-printing quality
- cleaning: easy to clean with CleanoMay 13, even when mounted



MayTex-PVC

- material: 79% chlorofibre, 21% polyester, weight 480 g/m² ± 5%
- water column (fabric water tightness) > 1000 mm, European standard EN 20811
- colour fastness: grade ≥ 7 (against bleaching), tested acc. to standard EN ISO 105-B02 (1= min., 8= max.)
- flammability "flame retardant"
 - "B1" German standard DIN 4102-1
 - "M2" French standard NF P92-503
 - "CL2" Italian standard RF 1-75 E 3-77
- protection against UV rays: UPF80, tested acc. to UV standard 801 (cf. page 135 for individual values)
- Texgard impregnation gives effective protection against oil, grease, mildew and algae, industrial pollution, exhaust fumes and other negative environmental factors
- in accordance with REACH
- 100% recyclable (to be returned to May Gerätebau GmbH)
- imprinted ads. on parasol canopy and valance in durable, brilliant screen-printing quality
- cleaning: easy to clean with CleanoMay 13, even when mounted



On request we can also supply parasols for indoor use with further flame retardant fabrics acc. to DIN 4102-1 B1.
The shades shown here are not in accordance with the original ones. If requested, we will be pleased to send you a collection of original cloth samples.

If no colour is specified, a binding tape will be chosen to match the cloth.



The shades shown here are not in accordance with the original ones. If requested, we will be pleased to send you a collection of original cloth samples.